

# Shred-Truck Range

## Asia



Specification	MST-8 Fuso	MST-8 Hino
Chassis	FUSO Canter 7C15 Duonic	HINO 300 Series
GVW	7,500 kg	7,500 kg
HP - kW	110 kW	121 kW
Transmission	Duonic Auto 6 speed	MY6S
Exhaust	Horizontal	Horizontal
Fuel Capacity	100 litres	170 litres
Wheelbase	4,300 mm	4,400 mm
Cold Package	Standard	Standard
Interior***	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning
Payload*	2,000 kg	2,000 kg
Overall Length	7,185 mm	7,250 mm
Overall Height	3,400 mm	3,400 mm
Body Width	2,206 mm	2,206 mm
Truck Body	GRP	GRP
Shredder Equipment	MST-8 Fuso	MST-8 Hino
Shredder Module	FATSO-500	FATSO-500
Shafts	10 / 12 / 16 mm	10 / 12 / 16 mm
Throughput**	up to 1,000 / 1,250 / 1,500 (kg / hr)	up to 1,000 / 1,250 / 1,500 (kg / hr)
Gearboxes	Direct Drive Planetary per shaft	Direct Drive Planetary per shaft
Standard Features	MST-8 Fuso	MST-8 Hino
Bin Handling	Side Lifter and Bin Tipper	Side Lifter and Bin Tipper
Live Floor Unload	Walking Floor	Walking Floor
Entry Door	Swing Door	Swing Door
Curbside Control	Engine Start Stop / PTO	Engine Start Stop / PTO
Feed System	Hopper	Hopper
Unload Control	Outside Body Mounted	Outside Body Mounted
Diagnostic	Service Diagnostic Help Screen	Service Diagnostic Help Screen
Optional Extras	MST-8 Fuso	MST-8 Hino
Service Program	Optional	Optional
Weight Scale	Optional	Optional
Custom Paint and Graphics	Optional	Optional
Reverse Camera	Optional	Optional
Swing Entry Door	Optional	Optional
Wind Deflector	Optional	Optional

\* Payload is based on Cab-Chassis weights and specs from Manufacturers at time of print. Check with AXO at time of ordering regarding exact weights.

\*\* Throughput figures vary according to feed method & product type being shredded, system maintenance and operator training. \*\*\* Subject to Manufacturers Specification