

Shred-Truck Range

UK/Europe

Specification	MST-8	MST-12	MST-18	MST-18 K-Lift
Chassis	FUSO Canter 7C15 Duonic	MAN TGL 12t	MAN TGM 18t	MAN TGM 18t
GVW	7,500 kg	12,000 kg	18,000 kg	18,000 kg
HP - kW	110 kW	250 HP	250 HP	250 HP
Transmission	Duonic Auto 6 speed	AS Tronic Automated 12 Speed	AS Tronic Automated 12 Speed	AS Tronic Automated 12 Speed
Exhaust	Horizontal	Horizontal	Horizontal	Horizontal
Fuel Capacity	100 litres	150 litres	300 litres	300 litres
Wheelbase	4,300 mm	5,200 mm	6,175 mm	6,175 mm
Cold Package	Standard	Standard	Standard	Standard
Interior***	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning	Radio-CD Player / PW / AC / Cruise Control / Reverse Warning
Payload*	2,000 kg	4,500 kg	6,000 kg	6,000 kg
Overall Length	7,185 mm	8,600 mm	9,640 mm	9,640 mm
Overall Height	3,400 mm	3,880 mm	3,880 mm	3,880 mm
Body Width	2,206 mm	2,456 mm	2,540 mm	2,540 mm
Truck Body	GRP	GRP	GRP	GRP
Shredder Equipment	MST-8	MST-12	MST-18	MST-18 K-Lift
Shredder Module	FATSO-500	FATSO-500	FATSO-500	FATSO-500
Shafts	10 / 12 / 16 mm	10 / 12 / 16 mm	16 mm	16 mm
Throughput**	up to 1,000 / 1,250 / 1,500 (kg / hr)	up to 2,000 kg / hr	up to 2,500 kg / hr	up to 2,500 kg / hr
Gearboxes	Direct Drive Planetary per shaft	Direct Drive Planetary per shaft	Direct Drive Planetary per shaft	Direct Drive Planetary per shaft
Standard Features	MST-8	MST-12	MST-18	MST-18 K-Lift
Bin Handling	Side Lifter and Bin Tipper	Side Lifter	Side Lifter	Kerb Lifting System
Live Floor Unload	Walking Floor	Walking Floor	Walking Floor	Walking Floor
Entry Door	Swing Door	Swing Door	Swing Door	Shredder / Payload
Curbside Control	Engine Start Stop / PTO	Engine Start Stop / PTO	Engine Start Stop / PTO	Engine Start Stop / PTO
Feed System	Hopper	Level Feed	Level Feed	Level Feed
Unload Control	Outside Body Mounted	External and In Cab	External and In Cab	External and In Cab
Diagnostic	Service Diagnostic Help Screen	Service Diagnostic Help Screen	Service Diagnostic Help Screen	Service Diagnostic Help Screen
Optional Extras	MST-8	MST-12	MST-18	MST-18 K-Lift
Service Program	Optional	Optional	Optional	Optional
Weight Scale	Optional	Optional	Optional	Optional
Custom Paint and Graphics	Optional	Optional	Optional	Optional
Reverse Camera	Optional	Optional	Optional	Optional
Remote Unload	Optional	Optional	Optional	Optional
Wind Deflector	Optional	Optional	Optional	Optional

* Payload is based on Cab-Chassis weights and specs from Manufacturers at time of print. Check with AXO at time of ordering regarding exact weights.

** Throughput figures vary according to feed method & product type being shredded, system maintenance and operator training. *** Subject to Manufacturers Specification

Shred-Tech Asia Co., Ltd. (Thailand)
789/52 Moo 1, Nong-Kham, Sriracha, Chonburi, Thailand 20230
+66 3834 8250
info@shred-tech.asia | www.shred-tech.asia

Shred-Tech Corp. (Canada)
295 Pinebush Rd. Cambridge, Ontario Canada N1T 1B2
+1 (519) 621-3560
shred@shred-tech.com | www.shred-tech.com

Shred-Tech® Australasia (AU)
PO Box 620, South Yarra, Victoria 3141 Australia
+61 0498 730 684
justin@shred-tech.asia |